

天井吊露出ダクト接続形

UAHM90~450C(Z)

冷房能力

機種名		入口空気温度(℃) 入口水温(℃) 能力(kW) 水圧損失(kPa) 水量(ℓ/min)		26D.B. 18.6W.B.						27D.B. 19.5W.B.						27D.B. 21W.B.						28D.B. 22W.B.						
				5		7		9		5		7		9		5		7		9		5		7		9		
				全熱量	顕熱量	全熱量	顕熱量	全熱量	顕熱量	全熱量	顕熱量	全熱量	顕熱量	全熱量	顕熱量	全熱量	顕熱量	全熱量	顕熱量	全熱量	顕熱量	全熱量	顕熱量	全熱量	顕熱量	全熱量	顕熱量	
				18	8.8	8.95	6.86	7.79	6.51	6.63	6.16	9.65	7.09	8.49	6.74	7.21	6.28	10.70	6.51	9.53	6.05	8.37	5.70	11.63	6.63	10.47	6.28	9.19
UAHM90C(Z)	24	13.7	10.12	7.33	8.84	6.86	7.44	6.40	10.81	7.44	9.65	7.09	8.26	6.63	12.33	6.98	10.93	6.51	9.65	6.05	13.26	7.21	11.98	6.74	10.58	6.28	9.19	5.81
	30	19.6	10.93	7.56	9.53	7.09	8.14	6.63	11.74	7.79	10.47	7.33	8.95	6.86	13.37	7.44	11.98	6.86	10.47	6.28	14.42	7.67	13.02	7.09	11.63	6.63	9.19	5.81
	39	30.4	11.86	7.91	10.35	7.33	8.84	6.74	12.79	8.26	11.28	7.56	9.77	6.98	14.53	7.91	13.02	7.33	11.51	6.74	15.70	8.26	14.19	7.56	12.67	6.98	9.19	5.81
	48	43.1	12.44	8.26	10.93	7.56	9.30	6.86	13.49	8.49	11.98	7.91	10.35	7.21	15.35	8.26	13.84	7.67	12.09	6.98	16.63	8.60	15.00	7.91	13.37	7.33	9.19	5.81
UAHM150C(Z)	30	16.7	15.00	11.63	13.02	10.93	11.05	10.35	16.16	11.86	14.30	11.28	12.21	10.58	18.14	10.81	16.16	10.23	14.07	9.53	19.65	11.05	17.67	10.47	15.58	9.77	9.19	5.81
	40	26.5	16.86	12.09	14.77	11.40	12.56	10.70	18.26	12.44	16.16	11.74	13.84	11.05	20.58	11.74	18.49	10.93	16.16	10.12	22.33	12.09	20.12	11.28	17.79	10.47	9.19	5.81
	50	38.2	18.26	12.56	15.93	11.74	13.60	11.05	19.77	13.02	17.44	12.09	15.00	11.40	22.44	12.44	20.12	11.51	17.56	10.58	24.19	12.91	21.86	11.98	19.42	11.05	9.19	5.81
	65	60.8	19.77	13.14	17.33	12.09	14.53	11.16	21.40	13.72	18.95	12.67	16.28	11.63	24.19	13.26	21.74	12.21	19.19	11.16	26.28	13.72	23.72	12.67	21.16	11.63	9.19	5.81
UAHM225C(Z)	80	84.3	20.70	13.60	18.14	12.56	15.47	11.40	22.44	14.19	19.88	13.02	17.21	11.98	25.58	13.72	22.91	12.67	20.23	11.51	27.67	14.30	25.00	13.14	22.33	12.09	9.19	5.81
	45	10.8	22.33	17.56	19.53	16.63	16.51	15.70	24.07	18.02	21.28	17.09	18.26	16.16	27.09	16.28	24.07	21.28	20.93	14.53	29.19	16.74	26.28	15.81	23.14	14.88	9.19	5.81
	60	17.6	25.23	18.37	22.09	17.44	18.72	16.40	27.21	18.84	24.07	17.91	20.70	16.86	30.81	17.67	27.56	16.40	24.19	15.35	33.37	18.26	30.00	16.98	26.63	15.70	9.19	5.81
	75	25.5	27.33	18.95	23.95	17.91	20.35	16.74	29.65	19.65	26.16	18.37	22.56	17.33	33.60	18.84	30.12	17.44	26.40	16.05	36.28	19.42	32.79	18.02	29.07	16.63	9.19	5.81
UAHM300C(Z)	97.5	39.2	29.65	20.00	25.93	18.37	22.09	17.09	32.09	20.70	28.49	19.19	24.53	17.67	36.51	20.00	32.67	18.49	28.84	16.86	39.42	20.70	35.70	19.19	31.74	17.67	9.19	5.81
	120	55.9	31.28	20.70	27.44	19.07	23.37	17.33	33.95	21.51	30.12	19.88	25.93	18.14	38.49	20.81	34.65	19.19	30.47	17.56	42.91	21.63	37.79	20.00	33.60	18.14	9.19	5.81
	60	19.6	30.23	22.79	26.28	21.51	21.86	20.12	32.56	23.37	28.60	22.09	24.30	20.81	36.63	21.40	32.67	20.12	28.37	18.84	39.53	21.98	35.47	20.58	31.28	19.30	9.19	5.81
	80	31.4	33.84	23.84	29.65	22.44	25.00	20.93	36.63	24.42	32.09	23.14	27.79	21.74	41.40	23.26	37.09	21.51	32.44	19.88	44.77	23.95	40.35	22.33	35.70	20.58	9.19	5.81
UAHM375C(Z)	100	46.1	36.51	24.77	31.98	22.91	27.21	21.51	39.53	25.70	34.88	23.72	30.12	22.21	44.77	24.65	40.12	22.79	35.23	20.81	48.49	25.47	43.72	23.60	38.84	21.74	9.19	5.81
	120	62.7	36.05	25.58	33.60	23.49	28.60	21.74	41.74	26.63	36.86	24.53	31.74	22.56	47.33	25.70	42.44	23.72	37.21	21.63	51.16	26.63	46.28	24.65	41.05	22.56	9.19	5.81
	140	81.3	51.63	26.28	35.00	24.07	29.77	21.98	43.37	27.33	38.37	25.23	33.02	22.79	49.19	26.28	44.19	24.42	38.84	22.21	53.26	27.44	48.14	25.35	42.79	23.26	9.19	5.81
	75	4.9	36.98	28.95	32.44	27.33	27.67	25.70	39.65	29.77	35.12	28.14	30.23	26.40	44.19	27.21	39.42	25.47	34.42	23.84	47.67	27.79	42.79	26.16	37.67	24.53	9.19	5.81
UAHM450C(Z)	100	7.8	41.86	30.81	36.74	28.84	31.28	26.86	45.23	31.63	40.00	29.77	34.53	27.79	50.81	29.42	45.47	27.56	39.77	25.58	55.00	30.23	49.42	28.37	43.72	26.40	9.19	5.81
	125	11.8	45.58	32.09	40.00	30.00	34.19	27.91	49.30	33.14	43.60	31.05	37.67	28.95	55.81	31.40	49.88	29.07	43.84	26.86	60.23	32.33	54.42	30.12	48.26	27.79	9.19	5.81
	162.5	17.6	49.65	32.09	43.60	31.16	37.21	28.84	53.84	34.88	47.67	32.33	41.16	30.00	61.05	33.49	54.77	30.93	48.14	28.37	66.05	34.65	59.77	32.21	53.14	29.53	9.19	5.81
	200	25.5	52.67	33.60	46.16	32.09	39.42	29.53	57.09	36.28	50.58	33.49	43.72	30.81	64.77	35.12	58.26	32.33	51.28	29.53	70.12	36.40	63.37	33.60	56.51	30.93	9.19	5.81
UAHM450C(Z)	90	5.9	44.30	34.88	38.84	32.91	33.14	30.93	47.67	35.47	42.09	33.84	36.28	31.86	53.14	32.67	47.33	30.70	41.28	28.72	57.33	31.05	51.40	31.51	45.35	29.53	9.19	5.81
	120	9.8	50.23	36.74	44.07	34.77	37.56	32.44	52.91	38.02	47.90	35.81	41.28	33.49	61.05	35.35	54.53	33.02	47.67	30.70	65.81	36.40	59.42	34.07	52.56	31.74	9.19	5.81
	150	13.7	54.65	38.49	47.91	36.05	40.93	33.49	59.07	39.77	52.33	37.33	45.12	34.77	66.86	37.67	59.88	34.88	52.56	32.21	72.33	38.84	65.35	36.16	57.91	33.37	9.19	5.81
	195	20.6	59.53	40.35	52.21	37.44	44.53	34.77	64.53	41.86	57.09	38.84	49.30	36.05	73.14	40.23	65.70	37.21	57.79	34.07	79.19	41.63	71.63	38.60	63.72	35.58	9.19	5.81
UAHM450C(Z)	240	29.4	63.14	41.86	55.35	38.49	47.21	35.47	68.49	43.49	60.58	40.23	52.33	36.98	77.67	42.09	69.77	38.84	61.40	35.47	84.07	43.60	76.16	40.35	67.90	37.09	9.19	5.81

注) 風量はHの場合を示します。 内の数値は標準点を示します。 ※機種名の(Z)は右配管勝手仕様を示します。

暖房能力

機種名	入口空気温度(℃) 入口水温(℃) 能力(kW) 水压損失(kPa) 水量(ℓ/min)		18D.B.						20D.B.						22D.B.					
			40	45	50	60	70	80	40	45	50	60	70	80	40	45	50	60	70	80
			全熱量						全熱量						全熱量					
UAHM90C(Z)	18	8.8	7.79	9.53	11.28	14.88	18.37	21.98	7.09	8.84	10.58	14.19	17.67	21.28	6.40	8.14	9.88	13.49	16.98	20.47
	24	13.7	8.26	10.12	12.09	15.81	19.53	23.37	7.56	9.42	11.28	15.12	18.84	22.56	6.74	8.72	10.58	14.30	18.02	21.86
	30	19.6	8.60	10.58	12.56	16.40	20.35	24.30	7.79	9.77	11.74	15.70	19.53	23.49	7.09	8.95	10.93	14.88	18.84	22.67
	39	30.4	8.95	10.93	13.02	16.98	—	—	8.14	10.12	12.21	16.16	—	—	7.33	9.30	11.40	15.47	—	—
	48	43.1	9.07	11.16	13.26	17.44	—	0.00	8.26	10.35	12.44	16.63	—	—	7.44	9.53	11.63	15.81	—	—
UAHM150C(Z)	30	16.7	13.14	16.05	19.07	25.00	30.93	36.86	11.86	14.88	17.91	23.84	29.77	35.70	10.70	13.72	16.63	22.56	28.49	34.53
	40	26.5	13.84	17.09	20.23	26.51	32.91	—	12.67	15.81	18.95	25.23	31.63	—	11.40	14.53	17.67	23.95	30.35	—
	50	38.2	14.42	17.67	20.93	27.56	—	—	13.14	16.40	19.65	26.16	—	—	11.74	15.12	18.37	24.88	—	—
	65	59.8	14.88	18.26	21.74	28.49	—	—	13.60	16.98	20.35	27.09	—	—	12.21	15.58	18.95	25.81	—	—
	80	84.3	15.23	18.72	22.21	29.19	—	—	13.84	17.33	20.81	27.79	—	—	12.44	15.93	19.42	26.40	—	—
UAHM225C(Z)	45	10.8	19.65	24.07	28.49	37.44	46.28	55.23	17.79	22.33	26.74	35.58	44.53	53.37	16.05	20.47	24.88	33.84	42.79	51.62
	60	17.6	20.93	25.58	30.35	39.88	49.30	58.84	18.95	23.72	28.49	37.91	47.44	56.98	17.09	21.86	26.63	36.05	45.58	55.12
	75	25.5	21.74	26.63	31.63	41.51	—	—	19.77	24.65	29.65	39.53	—	—	17.79	22.67	27.67	37.56	—	—
	97.5	39.2	22.56	27.67	32.79	43.02	—	—	20.47	25.58	30.70	40.93	—	—	18.49	23.60	28.72	38.95	—	—
	120	55.9	23.02	28.37	33.60	44.07	—	—	20.93	26.28	31.51	41.98	—	—	18.84	24.07	29.42	39.88	—	—
UAHM300C(Z)	60	19.6	26.40	32.33	38.37	50.35	62.21	74.19	23.95	29.88	35.93	47.91	59.88	71.74	21.51	27.56	33.49	45.47	57.44	69.42
	80	31.4	27.79	34.19	40.47	53.14	—	—	25.35	31.63	38.02	50.58	—	—	22.79	29.07	35.47	48.14	—	—
	100	46.1	28.84	35.35	42.79	54.88	—	—	26.16	32.67	39.30	52.33	—	—	23.60	30.12	36.63	49.77	—	—
	120	62.7	29.42	36.16	43.49	56.16	—	—	26.74	33.49	40.12	53.49	—	—	24.07	30.81	37.44	50.81	—	—
	140	81.3	29.88	36.74	47.09	57.09	—	—	27.21	33.95	40.81	54.42	—	—	24.53	31.28	38.14	51.63	—	—
UAHM375C(Z)	75	4.9	32.33	39.65	47.09	61.74	76.40	91.16	29.42	36.74	44.07	58.84	73.49	88.26	26.51	33.84	41.16	55.81	70.58	85.23
	100	7.8	34.65	42.44	50.35	66.16	81.86	97.56	31.51	39.30	47.21	63.02	78.72	94.42	28.37	36.16	44.07	59.77	75.58	91.28
	125	11.8	36.05	44.30	52.56	68.95	85.35	101.74	32.79	41.05	49.19	65.70	82.09	98.49	29.53	37.79	45.93	62.33	78.84	95.23
	162.5	17.6	37.56	46.05	54.53	71.63	88.72	—	34.07	42.67	51.16	68.26	85.35	—	30.70	39.19	47.79	64.88	81.86	—
	200	25.5	38.49	47.21	55.93	73.37	—	—	35.00	43.72	52.44	69.88	—	—	—	40.23	48.95	66.40	—	—
UAHM450C(Z)	90	5.9	38.60	47.44	56.28	73.84	91.40	108.95	35.12	43.95	52.67	70.35	87.91	105.47	31.63	40.47	49.19	66.74	84.42	101.86
	120	9.8	41.40	50.81	60.23	78.95	97.79	116.63	37.67	46.98	56.51	75.23	94.07	112.91	33.84	43.26	52.67	71.51	90.35	109.07
	150	13.7	43.14	53.02	62.79	82.44	102.09	121.63	39.30	49.07	58.84	78.49	98.14	117.79	35.35	45.12	55.00	74.53	94.19	113.84
	195	20.6	44.88	55.12	65.35	85.70	—	—	40.81	51.05	61.16	81.63	—	—	36.74	46.98	57.21	77.56	—	—
	240	29.4	46.05	53.02	66.98	87.91	—	—	41.86	52.33	62.79	83.72	—	—	—	48.14	58.60	79.42	—	—